

T. 18 S., R. 63 E.

Chains

For instruments, observations and tests see Book "A" this group.

DEPENDENT RESURVEY OF THE EAST BDY. T. 18 S., R. 63 E.

REESTABLISHMENT OF THE SURVEYS EXECUTED BY  
W. H. MYRICK, Deputy Surveyor, in 1882.

From the cor. of Tps. 18 and 19 S., Rs. 63 and 64 E., which is an iron post, 3" diam., firmly set, properly marked and witnessed as described in Book "A".

N. 0°05' E., on record course and true line, bet. secs. 31 and 36.

Over rough hilly and mountainous land, through scattering undergrowth. Desc. rocky NW. slope,

- 3.10 Small rocky spur, projects W. and NW.; desc. abruptly 120 ft.
  - 11.40 Draw, drains W., over broken S. and SW. slopes.
  - 24.80 Small spur, projects W.
  - 28.60 Small spur, projects N. 30° W.; desc. 40 ft. over N. slope.
  - 40.00 Set an iron post 3 ft. long, 1 in. diam., 27 ins. in the ground, for  $\frac{1}{4}$  sec. cor., with brass cap marked
- $\frac{1}{4}$   
 S36 | S31  
 1933
- raise a mound of stone 5 ft. base, 3 ft. high, W. of cor.
  - 41.00 Small draw, heads 3 chs. NE., course S. 70° W.; asc. rocky S. slope.
  - 45.50 Small rocky spur, projects SW.; desc. rocky NW. slope, 40 ft.
  - 53.80 Large rocky draw, 30 lks. wide, course S. 30° W., precipitous sides 10 to 15 ft. high, composed of alternate layers of sandstone and limestone (sandstone predominating) in almost level strata.
  - Asc. steep, SE. slope, 130 ft. over loose slide rock.
  - 57:10 Rough, broken limestone ledges, 30 to 40 ft. high, bear NE. and S. 30° W.; desc. N. slope over exposed limestone strata dipping 20° west.
  - 60.00 Slope changes to a rocky broken E. slope.
  - 69.90 Spur, projects SW. from N. 30° W.; desc. broken, NE. slope.
  - 76.10 Head of a small gully, 70 ft. below spur, drains S. 60° E.; asc. 80 ft. over rocky E. slope.