

SUBDIVISION OF T. 18 S., R. 63 E.

Chains	
40.00	Set temp. $\frac{1}{4}$ sec. cor.
79.94	Intersect E. bdy. of Tp., 3 lks. N. of the cor. of secs. 1, 6, 7, and 12, which is an iron post 3 ins. diam. marked and witnessed as heretofore described. Thence N. $89^{\circ} 59'$ W., on true line bet. secs. 1 and 12; over flood plain, through dense undergrowth.
16.50	Dry channel, 30 lks. wide, 2 ft. deep, course N. 30° E.
39.97	Set an iron post 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
S1	
$\frac{1}{4}$	
S12	
1933	
60.20	raise a mound of stone 3 ft. base, 2 ft. high, north of cor. Small dry water channel, course N. 30° E.
64.00	Large dry water channel, 30 lks. wide, 2 to 3 ft. deep, course N. 60° E.
79.94	The cor. of secs. 1, 2, 11, and 12. Land, flood plain, gently sloping to the NE. Soil, sandy and gravelly, shallow clay loam; 3rd and 4th rate. Undergrowth, creosote, and cacti. No timber.
29.20	N. $0^{\circ} 04'$ E., on a true line bet. secs. 1 and 2. Uniform flood plain, through dense undergrowth.
40.00	Dry water channel, 10 lks. wide, 2 ft. deep, course N. 70° E.
40.00	Set an iron post 3 ft. long, 1 in. diam., 27 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap mkd.
$\frac{1}{4}$	
S2	
S1	
1933	
51.60	raise a mound of stone 3 ft. base, 2 ft. high, W. of cor. Dry water channel 10 lks. wide, 2 ft. deep, course E.
80.06	Intersect S. bdy. of Tp. 17 S., R. 63 E., N. $89^{\circ} 23'$ W. 1.50 chs. dist. from the cor. of secs. 35 and 36, which is an iron post 3 in. in diam., marked and witnessed as heretofore described. At point of intersection, Set an iron post 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 1 and 2, with brass cap marked