

SUBDIVISION OF T. 18 S., R. 63 E.

Chains

1933  
 raise a mound  
 of stone 3 ft. base, 2 ft. high, W. of cor.  
 47.80 Large dry channel, 60 lks. wide, 8 to 10 ft. deep, course  
 N. 80° E.  
 76.50 Dry wash, 15 lks. wide, 1 to 2 ft. deep, course E.  
 80.91 Intersect S. bdy. of Tp. 17 S., R. 63 E., N. 89° 23' W.,  
 3.00 chs. dist. from the cor. of secs. 34 and 35, which  
 is an iron post, 3 ins. diam., marked and witnessed, as  
 heretofore described.

At point of intersection,

Set an iron post 3 ft. long, 3 ins. diam., 27 ins. in the  
 ground, for closing cor. of secs. 2 and 3, with brass  
 cap mkd.

T17S R63E  
 S34

S3 | S2  
 cc

T18S R63E  
 1933

raise a mound  
 of stone 4 ft. base, 3 ft. high, S. of cor.

Land, flood plain, with uniform E. slope and drainage.  
 Soil, shallow, sandy to coarse gravelly loam; 3rd and  
 4th rate.  
 Undergrowth, creosote and cacti.  
 No timber.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy.  
 of Tp., which is an iron post, 3 ins. diam., marked and  
 witnessed, as described in Book "A", this group.

N. 0°03' E., bet. secs. 33 and 34.

Over rolling land, through medium dense undergrowth; desc.  
 along NE. slope of spur.

4.50 Small draw, drains E.; asc. 50 ft. over W. slope.  
 12.15 W. end of limestone butte; enter rolling hills along  
 broken E. slope; desc. gradually.  
 39.50 Head of small draw, drains E.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the  
 ground, for 1/4 sec. cor., with brass cap mkd.

S33 | S34

1933

raise a mound