

182

SUBDIVISION OF T. 18 S., R 63 E.

Chains

81.80

Intersect the S. bdy. of Tp. 17 S., R. 63 E., N. 89° 23' W., 4.46 chs. dist. from the cor. of secs. 33 and 34, which is an iron post 3 ins. diam., marked and witnessed, as heretofore described.

At point of intersection,

Set an iron post 3 ft. long, 3 ins. diam., 18 ins. in the ground to solid rock and with a limestone 8x6x2 ins., marked with cross (X), deposited at base, and in a large mound of stone for the closing corner of sections 3 and 4, with brass cap mkd.

T17S R63E

S33

S4 | S3

cc

T18S R63E

1933

raise a mound of stone 4 ft. base, 3 ft. high S. of cor.

Land, S. 1/2 rolling broken foot hills, N. 1/2 broken flood plains.

Soil, sandy and gravelly to rocky loam; 3rd and 4th rate.

Undergrowth, creosote and cacti.

No timber.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of Tp., which is an iron post 3 ins. diam., marked and witnessed as described in Book "A", this group.

N. 0° 02'E., bet. secs. 32 and 33.

Over broken hilly land, through medium dense undergrowth.

Desc. along rocky W. slope.

2.60

Small rocky draw, drains S. 20° W.; asc. 110 ft. over rocky SE. slope.

12.70

Rocky spur, projects S. 30° W.; continue along broken W. slope.

31.70

Draw, drains SW.; asc. 110 ft. over rocky broken S. slope, over limestone outcrops and ledges 8 to 10 ft. high.

40.00

Set an iron post, 3 ft. long, 1 in. diam. over a cross (X) cut on solid rock at exact corner point, in a large mound of stone, for 1/4 sec. cor., with brass cap mkd.

S32 | S33

1933

This cor. is set at the base of a 3 ft. limestone ledge bearing N. 20° E. and S. 20° E., on the edge of a spur projecting S. 60° W.

Continue along rocky W. slope.

45.00

Head of draw, drains SW.; asc. 200 ft. over broken SW. slope.