


SUBDIVISION OF T. 18 S., R. 63 E.

Chains

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



1933

raise a mound of stone 3 ft. base, 2 ft. high, W. of cor.

48.00 Low indistinct divide bet. drainage basins to the N. and S., bears E. and NW.; continue over flood plain, crossing numerous dry water channels, draining E. and SE.

82.61 Intersect S. bdy. of Tp. 17 S., R. 63 E., N. 89° 23' W. 5.87 chs. dist. from the cor. of secs. 32 and 33, which is an iron post 3 ins. diam., marked and witnessed, as heretofore described.

At point of intersection,

Set an iron post 3 ft. long, 3 ins. diam., 27 ins. in the ground, for the closing cor. of secs. 4 and 5, with brass cap mkd.

T17S R63E
S32



T18S R63E
1933

raise a mound of stone 5 ft. base, 3 ft. high, S. of cor.

Land, broken alluvial fans and flood plains.
Soil, sandy to gravelly loam; 3rd and 4th rate.
Undergrowth, creosote and cacti.
No timber.

From the cor. of secs. 5, 6, 31, and 32 on the S. bdy. of the Tp., which is an iron post, 3 ins. diam., marked and witnessed as described in Book "A", this group N. 0°02' E., on true line bet. secs. 31 and 32.

Asc. 40 ft. over rocky broken E. slope, through medium dense undergrowth.

9.40 Rocky spur, projects N. from S. 20° W.; desc. along top of spur.

19.40 Leave top of spur, which projects NE.; desc. broken rocky NW. slope.

34.70 Rocky draw, 470 ft. below rocky spur, drains N. 60° E.; continue along rocky SE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.



1933

This corner is situated on crest of main divide bearing N. 60° E. and S. 60° W.

Desc. 80 ft. over NW. slope.

48.20 Dry wash, 15 lks. wide, 4 ft. deep, course N. 60° E.; asc. 20 ft. over SE. slope.