

SUBDIVISION OF T. 18 S., R. 63 E.

Chains

- of stone 4 ft. base, 3 ft. high, N. of cor.
- 40.00 True point for cor. falls on rocky E. slope, 280 ft. above sec. cor.; continue ascent over rocky E. slope 250 ft.
- 49.70 Small rocky spur, projects NE., continue along a rocky E. slope.
- 55.50 Head of rocky gully, drains NE.
- 58.00 Top of limestone ledges, bearing N. and S. 70° W., on top of spur projecting NE., 110 ft. above small rocky spur; desc. 170 ft. over precipitous NW. slope to draw.
- 65.10 Base of limestone ledges on point of spur from the SE.
- 68.30 Rocky draw, drains NE.; asc. 30 ft. over rocky E. slope along bottom of small draw from the W.
- 69.73 Intersect W. bdy. of Tp., S. 4.13 chs. dist. from the cor. of secs. 25 and 36, which is an iron post, 2 ins. diam. mkd. and witnessed as heretofore described.
- At point of intersection,
- Set an iron post 3 ft. long, 2 ins. diam., over a cross (X) cut on exposed bedrock at exact cor. point and in a large mound of stone, for the closing cor. of secs. 30 and 31, with brass cap mkd.
- T18S

R62E		R63E
		S30c
S36		S31

1933
- from which
- a flat top limestone ledge, the smoothest surface of which, bears S. 78° 57' W., 35½ lks. dist., mkd. S.36 B.O.X.
- A deep cross is cut on limestone ledge on line S. 13½ lks. dist.
- Land, rough, hilly and broken mountainous.
Soil, shallow, rocky loam; 3rd and 4th rate.
Undergrowth, creosote, buckbrush and cacti.
No timber.
-
- N. 0°02' E., bet. secs. 29 and 30.
- Desc. 60 ft. gradually over an alluvial fan sloping N., through dense undergrowth.
- 24.30 Junction of washes from NW. and S. 15° W., drains NE.
- 27.80 Rocky point of spur from N. 15° W.; continue along rocky E. slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 6 ins. in the