

## SUBDIVISION OF T. 18 S., R. 63 E.

## Chains

Cross (X) cut on solid rock at base of post.

From this cor. the  $\frac{1}{4}$  sec. cor. of sec. 13, T. 18 S., R. 62 E., heretofore described bears North 4.10 chs. dist.

Establishment of the  $\frac{1}{4}$  sec. cor. for sec. 7, on the W. bdy. of T. 18 S., R. 63 E.

At midpoint between the closing cor. of secs. 7 and 18, and the closing cor. of secs. 6 and 7, heretofore described.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground to solid rock in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S7

raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.

From this cor. the  $\frac{1}{4}$  sec. cor. of sec. 12, T. 18 S., R. 62 E., heretofore described bears North, 4.13 chs. dist.

Establishment of the  $\frac{1}{4}$  sec. cor. for sec. 6, on the W. bdy. of T. 18 S., R. 63 E.

At a point 40.00 chs. North of the closing cor. of secs. 6 and 7, heretofore described.

Set an iron post, 3 ft. long, 1 in. diam., 10 ins. in the ground to solid rock, in a mound of stone, for  $\frac{1}{4}$  sec. cor., with brass cap mkd.

S6

Cross (X) cut on solid rock at base of post.

From this cor. the  $\frac{1}{4}$  sec. cor. of sec. 1, T. 18 S., R. 62 E., heretofore described bears North 4.16 chs. dist.

## GENERAL DESCRIPTION

This township contains two types of land forms: plains of alluvial deposition that cover about two-thirds of the surface, and hills and mountains. The lowest point is the northeast corner at an elevation of about 2,000 feet and from which the plains gradually rise to the south and west, the highest point is along the rocky west boundary at an elevation of about 3,500 feet. The plains usually have a fairly even