. Dependent Resurvey of the East Boundary of T. 3 N. . R. 57 E.

Chains	
	entest0
TOPYON	quede 20 '02 . and TRUE LINES and . seek are '02 . 33 . Sharp,
. 50 i.e.	Beginning at the corner of Tps. 2 and 3 N., Rs. 57 and 58 E., which is marked by a basalt stone 4x4x2 ins. lying on a small mound of earth and stone, and marked dimly with 6 notches on two opposite faces.
	At the corner point, sand days
	Set an iron post, 3 feet long, 3 inches in diameter, 30 ins. in the ground for the corner of Tps. 2 and 3 N., Rs. 57 and 58 E., with brass cap marked:
	T3N R57E R58E S36 S31
s Alim I	Doposit o since son consideration of the post of the constant
of early for to	Deposit the original corner stone alongside the post. Thence
	N. 1°24' W., along the W. boundary of section 31, T. 3 N., R. 58 E.
. 30 Ma. Al. 11 8	Over nearly level land; with a gentle SE. slope, through dense undergrowth.
22.00	Small wash, drains SE.
40.00	Set an iron post, 3 ft. long, 1 in. in diameter, 30 ins. in the ground, for the 4 section corner of section 36 T. 3 N., R. 57 E., with brass cap marked:
	\$836
. Jecg cas	Deceate thereal corner stone alongeide
.x.d.l. ak	Deposit a limestone rock, 5x4x2 ins. marked with a cross (X) at the base of the post. No other suitable accessory available.
40.69	Intersect the original $\frac{1}{4}$ section corner, a basalt stone, $7x5x3$ ins. marked $\frac{1}{4}$ on the top face, lying on a mound of earth.
	At the corner point,
1	Set an iron post, 3 ft. long and one in. in diameter, 25 ins. in the ground, and in a mound of stone; for the \(\frac{1}{4}\) section corner of section 31 T. 3 N., R. 58 E., with brass cap marked:
	• colore • con an compa sance
	1.831 spetora . Tade wal 08.1
	Deposit the original corner stone at the base of the post.
as . A est	
ond ich en	N. 0°09' E., with continuous measurement.
	inomen des sens
	Busé

6-815

EXE I