


292

Dependent Resurvey of the East Boundary of T. 3 N., R. 57 E.

Chains

At the corner point, Set an iron post, 3 ft. long and 3 ins. in diameter, 30 ins. in the ground, for the corner of Tps. 3 and 4, N., Rs. 57 and 58 E., with brass cap marked:



T3N

- A pinon, 5 ins. in diameter, marked T4NR58E31BT, bears N. 51°00' E., 102 links distant.
- A pinon, 8 ins. in diameter, marked T3NR58E36BT, bears S. 36°45' E., 74 links distant.
- A pinon, 4 ins. in diameter, marked BT, bears S. 42°30' W., 56 links distant.
- A juniper, 3 ins. in diameter, marked BT, bears N. 22°45' W., 67 links distant.

Deposit the original corner stone alongside the iron post.

Land: Rolling bench; SE. exposure and drainage.  
 Soil: Gravelly to rocky loam, 3rd. rate.  
 Timber: Juniper and pinon.  
 Undergrowth: Sagebrush. Bunch grass.  
 Fair grazing.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY OF T. 3 N., R. 57 E.

Superseding the Survey Executed by Reilly and Magee in 1881.

RANDOM LINES.

Beginning at the corner of Tps. 2 and 3, N., Rs. 57 and 58 E., heretofore described.

Thence

West, between sections 1 and 36.

40.36. Fall 12 links north of the original 1/4 section corner, hereinafter described.

The true course of this half mile is, therefore, S. 89°50' W., and the distance is 40.36 chains.

Offset to the 1/4 section corner and continue West with continuous measurement.

80.48. Fall 2 links north of the original corner of sections 1, 2, 35, and 36, hereinafter described.