

Dependent Resurvey of the South Boundary of T. 3 N., R. 57 E.

Chains

ins. in the ground to solid rock, in a mound of stone, for the corner of sections 5 and 6, T. 2 N., R. 57 E., with brass cap marked:

T3NR57E
S31

S6 | S5
T2N
1933

Deposit the original corner stone alongside the iron post.

Land: Low rolling bench; SE. exposure and drainage.
Soil: Gravelly to rocky loam; 3rd rate.
No timber.
Undergrowth: Sagebrush. Bunch grass.
Fair grazing.

N. 89°25' W., along the north boundary of section 6, T. 2 N., R. 57 E.

Over low rolling foothills, through widely scattered timber and dense undergrowth; ascend 125 ft. over an E. slope.

11.20 Spur, projects SE.; descend 180 ft. along a rocky SW. slope.

24.00 Draw, drains S. 15° E.

37.47 On the top of a spur projecting SE.

Set an iron post, 3 ft. long and 1 in. in diameter, 25 ins. in the ground to solid rock, and in a mound of stone for the 1/4 section corner of section 31 T. 3 N., 57 E., with brass cap marked:

1/4 S31

1933

Deposit a basalt stone, 4x3x2 ins., marked with a cross (X), at the base of the post. No other suitable accessory available.

Descend 10 ft. along a SE. slope.

40.13 Intersect the original 1/4 section corner, a basalt stone, 8x6x2 ins., set in a mound of stone, and marked 1/4 on the north face.

At the corner point,

Set an iron post, 3 ft. long and 1 in. in diameter, 20 ins. in the ground to solid rock, and in a mound of stone for the 1/4 section corner of section 6, T. 2 N., R. 57 E., with brass cap marked:

1/4 S6

1933

whence