

318

SUBDIVISION OF T. 3 N., R. 57 E.

Chains

SUBDIVISION OF T. 3 N., R. 57 E.

The first meridional section line is surveyed N. 0°10' W. as a governing section line parallel to the mean course of the east boundary.

Beginning at the corner of sections 35 and 36, on the south boundary of the township heretofore described.

Thence

N. 0°10' W., between sections 35 and 36.

Over nearly level bench land, through a dense undergrowth.


15.00 Small wash, drains SE.

31.80 Low spur, projects SE.

37.50 Shallow wash, drains SE.

40.00 On a gentle S. slope,

Set an iron post, 3 ft. long and 1 in. in diameter, 30 ins. in the ground, for the 1/4 section corner, with brass cap marked:



Deposit a limestone rock, 6x4x2 ins., marked with a cross (X), at the base of the post. No other suitable accessory available.

46.20 Low spur, projects SE.

50.00 Shallow wash, drains SE.

65.00- Low spur, projects SE.

68.20 Shallow wash, drains SE.

75.00 Low spur, projects SE.

80.00 On a gentle NE. slope,

Set an iron post, 3 ft. long and 2 ins. in diameter, 30 ins. in the ground, for the corner of sections 25, 26, 35, and 36, with brass cap marked:



Deposit a limestone rock, 6x2x2 ins., marked with a cross (X), at the base of the post. No other suitable accessory available.

Land: Nearly level bench; slight SE. exposure and drainage.

Soil: Deep sandy loam; 1st rate.

No timber.