

Subdivision of T. 3 N., R. 57 E.

Chains

6.40 Draw, drains NE.; ascend 175 ft. over an E. slope.

29.00 Spur, projects N. 30° E.; descend 90 ft. along a NW. slope.

34.60 Draw, drains N. 20° E.; ascend 95 ft. over an E. slope.

40.00 On an E. slope,

Set an iron post, 3 ft. long and 1 in. in diameter, 16 ins. in the ground, and in a mound of stone, for the 1/4 section corner, with brass cap marked:

S19

S30

1933

from which

A pinon, 8 ins. in diameter, marked 1/4S30BT, bears S. 15°45' E., 68 links distant.

A pinon, 10 ins. in diameter, marked 1/4S19BT, bears N. 76°20' E., 49 links distant.

Ascend 215 ft. over a rocky E. slope.

50.30 Spur, projects NE.; descend 45 ft. along a NW. slope.

56.80 Draw, drains NE.; ascend 140 ft. along a SE. slope.

66.30 Spur, projects NE.; descend 20 ft. along a NW. slope.

72.60 Head of a draw draining NE.; ascend 115 ft. along a NE. slope.

79.10 Ridge, bears NW. and SE., divide between Cherry and Pine Creeks. Descend along a rocky SW. slope.

82.66 Intersect the west boundary of the township at a point 1.51 chains N. of the corner of sections 24 and 25, T. 3 N., R. 56 E., heretofore described.

At the point of intersection,

Set an iron post, 3 ft. long and 2 ins. in diameter, 30 ins. in the ground for the closing corner of sections 19 and 30, T. 3 N., R. 57 E., with brass cap marked:

T3N R56E R57E

S19

S24 CC

S30

1933

whence

A pinon, 4 ins. in diameter, marked CCBT, bears N. 13°30' E., 95 links distant.

A pinon, 3 ins. in diameter, marked CCBT, bears S. 35°15' E., 70 links distant.

Land, rough and broken mountain slopes; general NE. exposure and drainage.