

372

Subdivision of T. 3 N., R. 57 E.

Chains

A pinon, 3 ins. in diameter, marked BT, bears S. 54°30' E., 12 links distant.

A pinon, 3 ins. in diameter, marked BT, bears N. 26°15' W., 24 links distant.

Descend 30 ft. along a NW. slope.

42.30 Draw, drains NE.; ascend 35 ft. along a SE. slope.

55.80 Point of a spur projecting from the N.; descend 60 ft. along a SW. slope.

63.50 Draw, drains SE.; ascend 185 ft. along the top of a spur projecting from the W.

80.14 The corner of sections 17, 18, 19, and 20.

Land, rolling mountain slopes; general NE. exposure and drainage.

Soil: Shallow gravelly loam; 2nd rate.

Timber: Pinon and juniper.

Undergrowth: Sagebrush, buck brush and mountain rush. Bunch grass.

Good grazing.

West, on true line between sections 18 and 19.

Over mountainous land, through dense timber and a medium dense undergrowth. Ascend 370 ft. over a rocky E. slope along the top of a spur projecting from the W.

13.50 Ridge, bears NW. and SE.; descend 130 ft. along a rocky SW. slope.

28.50 Draw, drains SE.; ascend 155 ft. along a NE. slope.

40.00 On a NE. slope,

Set an iron post, 3 ft. long and 1 in. in diameter, 26 ins. in the ground, and in a mound of stone, for the 1/4 section corner, with brass cap marked:

18

19

1933

whence

A pinon, 6 ins. in diameter, marked 1/4 S19BT, bears S. 13°00' E., 81 links distant.

A pinon, 4 ins. in diameter, marked 1/4 S18BT, bears N. 56°45' W., 44 links distant.

Ascend 650 ft. over an E. slope to the closing section corner.

60.00 Spur, projects SE.; continue ascent along SE. slope.

82.47 Intersect the W. boundary of the township at a point 1.54 chains N. of the corner of sections 13 and 24