

576

Subdivision of T. 3 N., R. 57 E.

Chains

74.00 Spur, projects SE.; descend 145 ft. along a SE. slope.

80.20 The corner of sections 7, 8, 17, and 18. Land: Rough mountain slopes, small patch of arable land along the bottom of Cherry Creek; general SE. exposure and drainage. Soil: Sandy to rocky loam; 1st and 3rd rate. Timber: Pinon, juniper and mahogany. Undergrowth: Sagebrush, buck brush and mountain rush. Bunch grass. Fair grazing.

West, on true line between sections 7 and 18.

Over mountainous land, through dense timber and a medium dense undergrowth. Descend 25 ft. along a SW. slope.

4.20 Draw, drains SE.; ascend 390 ft. along a NE. slope.

40.00 Spurs, project N. 70° E. and S. 70° E. from the SW.

Set an iron post, 3 ft. long and 1 in. in diameter, 16 ins. in the ground to solid rock, and in a mound of stone, for the 1/4 section corner, with brass cap marked:

1/4 S7  
S18  
1933

whence

A pinon, 8 ins. in diameter, marked 1/4 S18BT, bears S. 31°15' W., 100 links distant.

A pinon, 16 ins. in diameter, marked 1/4 S7BT, bears N. 39°30' W., 26 links distant.

Ascend 415 ft. to the closing section corner; ascend along a NE. slope.

50.60 Spur, projects SE.; continue ascent along a SE. slope.

65.00 Same spur, projects NE.; continue along a NE. slope.

82.00 The same spur, projects SE.; continue along the S. slope.

82.22 Intersect the west boundary of the township at a point 1.52 chains N. of the corner of sections 12 and 13, T. 3 N., R. 56 E., heretofore described.

At the point of intersection, Set an iron post, 3 ft. long and 2 ins. in diameter, 29 ins. in the ground, for the closing corner of sections 7 and 18, T. 3 N., R. 57 E., with brass cap marked:

T3N  
R56E | R57E  
S7  
S12 | CC  
S18  
1933

whence