

380

Subdivision of T. 13 N., R. 157 E.

Chains

A pinon, 3 ins. in diameter, marked BT, bears N. 10°00' W., 32 links distant.

Ascend 380 ft. along a steep NE. slope.

61.80 Spur, projects NE.; descend 25 ft. along a NW. slope.

66.80 Small draw, drains NE.; ascend 145 ft. along a NE. slope.

73.30 Spur, projects NE.; descend 25 ft. along a NW. slope.

77.00 Small draw, drains N.; ascend 120 ft. along a NE. slope.

81.84 Intersect west boundary of the township at a point 1.54 chains N. of the corner of sections 1 and 12, T. 3 N., R. 56 E., heretofore described.

At the point of intersection,

Set an iron post, 3 ft. long and 2 ins. in diameter, 30 ins. in the ground for the corner of sections 6 and 7, T. 3 N., R. 57 E., with brass cap marked:

T3N	
R56E	R57E
S1	S6
	CC
	S7
	1933

whence

A pinon, 24 ins. in diameter, marked T3NR57ES6CCBT, bears N. 43°38' E., 32 links distant.

A juniper, 4 ins. in diameter, marked BT, bears S. 28°30' E., 44 links distant.

Land: Rough and broken mountain slopes; general SE. exposure and drainage.

Soil: Sandy to rocky loam; 1st and 3rd rate.

Timber: Pinon and juniper.

Undergrowth: Sagebrush, buck brush and mountain rush.

Bunch grass.

Fair grazing.

Beginning at the corner of sections 5, 6, 7, and 8.

Thence

N. 0°12' W., on a random line between sections 5 and 6.

40.00 Set a temporary 1/4 section corner.

84.45 Intersect the N. boundary of the township at a point 10 links W. of the corner of sections 5, 6, 31, and 32, heretofore described.

Thence

S. 0°08' E. on true line between sections 5 and 6.