

Subdivision of T. 3 N., R. 57 E.

Chains

- Descend 25 ft. along a SE. slope.
- 5.80 Draw, drains SW.; ascend 450 ft. along a rocky NW. slope.
- 23.00 Spur, projects S. 15°00' W., from the NE.; descend 560 ft. along a SE. slope.
- 44.45 On a rocky SE. slope,
- Set an iron post, 3 ft. long and 1 in. in diameter, 12 ins. in the ground to solid rock, and in a mound of stone, for the $\frac{1}{4}$ section corner, with brass cap marked:
- S6 | S5
1933
- whence
- A pinon, 10 ins. in diameter, marked $\frac{1}{4}$ S5BT, bears N. 44°30' E., 51 links distant.
- A pinon, 8 ins. in diameter, marked $\frac{1}{4}$ S6BT, bears S. 17°00' W., 40 links distant.
- Descend 260 ft. along a SE. slope.
- 51.35 Draw, drains SW.; ascend 45 ft. along a NE. slope.
- 63.85 Spur, projects SW.; descend 145 ft. along a SE. slope.
- 72.85 Draw, drains SW.; ascend 45 ft. along a NW. slope.
- 84.45 The corner of sections 5, 6, 7, and 8.

Land: Steep and rugged mountain slopes; general SW. exposure and drainage.
 Soil: Shallow gravelly to rocky loam; 3rd rate.
 Timber: Pinon, mahogany and juniper.
 Undergrowth: Sagebrush, mountain rush and buck brush.
 Fair grazing.

Establishment of the $\frac{1}{4}$ Section Corner Between Closing
 Corners on the West Boundary of T. 3 N., R. 57 E.

At a point 1.33 chains N. of the $\frac{1}{4}$ section corner of section 36, T. 3 N., R. 56 E., heretofore described, and 40 chains S. of the closing corner of sections 30 and 31, T. 3 N., R. 57 E., heretofore described,

Set an iron post, 3 ft. long and 1 in. in diameter, 8 ins. in the ground to solid rock, and in a mound of stone, for the $\frac{1}{4}$ section corner of section 31, T. 3 N., R. 57 E., with brass cap marked:

1931

1933

whence