

INDEPENDENT RESURVEY, 3RD STAN. PAR. S., S. BDY. T12S R66E

Chains

40.00 S. 1 lk. from the secant,
Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in the ground, for standard 1/4 sec. cor., with brass cap mkd.

SC
1/4 S 35

1934

raise a mound

of stone, 3 ft. base, 2 ft. high, N. of cor.

45.40 Dry wash, 20 lks. wide, 6 to 8 ft. deep, drains SW.

Diff. bet. meas. of 80.00 chs., by two sets of chainmen, is 1 lk.; position of middle point--
By 1st set, 80.005 chs.
By 2nd set, 79.995 chs., the mean of which is

80.00 On the secant,
Set an iron post, 3 ft. long, 2 ins. in diam., 30 ins. in the ground, for standard cor. of secs. 35 and 36, with brass cap mkd.

S C
T12S R66E
S35 S36

1934

raise a mound

of stone, 4 ft. base, 3 ft. high, N. of cor.

Land, rolling.

Soil, coarse gravelly and rocky clay loam, 3rd and 4th rate.

Undergrowth, cacti, creosote brush.

No timber.

East, along the S. bdy. of sec. 36, on a transit line describing the secant which bears S. 89° 58.7' E.

Over gently rolling bench land through medium to dense undergrowth. Asc. gradual uniform SW. slope.

Diff. bet. meas. of 40.00 chs., by two sets of chainmen, is 2 lks.; position of middle point--
By 1st set, 40.01 chs.
By 2nd set, 39.99 chs., the mean of which is

40.00 N. 2 lks. from the secant,
Set an iron post, 3 ft. long, 1 in. in diam., 30 ins. in the ground, for standard 1/4 sec. cor., with brass cap mkd.

SC
1/4 S 36

1934