

INDEPENDENT RESURVEY, 3RD STAN. PAR., S., S.BDY. T12S R67E

Chains

Diff. bet. meas. of 80.00 chs., by two sets of chainmen, is nothing.

80.00

On the secant,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, for the standard cor. of secs. 35 and 36, with brass cap mkd.

SC

T12SR67E

S 35 S 36

1934

raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.

Land, W. 50 chs. rough mountainous; balance of mile, rough broken hilly.

Soil, shallow rocky clay loam, 3rd and 4th rate.

Undergrowth, cacti, creosote, greasewood, shadscale.

No timber.

East, along the S. bdy. of Sec. 36, on a transit line describing the secant, which bears S.89°58.7'E.

Over broken hilly land thru scattering undergrowth.

Asc. 120 ft. over general SW. slope.

13.90

Rocky spur, slopes S., desc. 200 ft. over broken E. slope.

29.80

Draw, drains S.60°E., asc. 50 ft. over SW. slope.

Diff. bet. meas. of 40.00 chs., by two sets of chainmen, is 2 lks., position of the middle point--

By 1st set, 40.01 chs.

By 2nd set, 39.99 chs., the mean of which is

40.00

N. 2 lks. from the secant,

Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to bedrock and supported in a mound of stone to the top, for the standard 1/4 sec. cor., with brass cap mkd.

SC

1/4 S 36

1934

Deposit a limestone, 4x4x6 ins., marked cross (x) at base of post.

Asc. 30 ft. over SW. slope.

41.30

Small rocky spur, slopes S.60°E., desc. 200 ft. over broken E. slope.

72.00

Main draw, drains S.60°E., continue descent of broken E. slope 60 ft.

Diff. bet. meas. of 80.00 chs., by two sets of chainmen, is nothing.

80.00

N. 4 lks. from the secant,