

INDEPENDENT RESURVEY 3RD STAN. PAR. S., S. BDY. T12S R70E

Chains

Diff. bet. meas. of 80.00 chs., by two sets of chainmen, is 3 lks.; position of middle point-----  
By 1st set, 80.015 chs.  
By 2nd set, 79.985 chs., the mean of which is

80.00 On the secant,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the standard cor. of secs. 35 and 36, with brass cap mkd.

SC  
T12S R70E

S 35 | S 36

1934

and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

This cor. stands on steep SE. slope. Land, rolling mesa and broken hilly slopes. Soil, shallow sandy loam to rocky loam, 3rd rate. Undergrowth, cacti, creosote, greasewood, shadscale. No timber.

East, along the S. bdy. of Sec. 36, on a transit line describing the secant, which bears S. 89°58.7'E.

Over broken hilly land thru scattering undergrowth. Desc. 280 ft. over SE. slope.

31.90 Wide dry wash, 200 lks. wide, 80 to 100 ft. deep, drains S.

Diff. bet. meas. of 40.00 chs., by two sets of chainmen, is nothing.

40.00 N. 2 lks. from the secant,

Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the standard sec. cor., with brass cap mkd.

SC  
S 36

1934

and raise a mound of stone, 4 ft. base, 3 ft. high, N. of cor.

Continue over broken SE. slope; desc. 40 ft.

51.90 Dry wash, 30 lks. wide, 10 ft. deep, course S., asc. 230 ft. over rough choppy SW. slopes.

Diff. bet. meas. of 80.00 chs., by two sets of chainmen, is 4 lks.; position of middle point-----

By 1st set, 40.02 chs.,  
By 2nd set, 39.98 chs., the mean of which is

80.00 N. 4 lks. from the secant,

Set an iron post, 3 ft. long, 3 ins. diam., 27 ins. in the ground for the standard cor. of Tps. 12 S., Rs. 70 and 71 E., with brass cap mkd.