

INDEPENDENT RESURVEY OF
OF THE RANGE LINE THROUGH T. 15 S., BETWEEN RS. 70 AND 71 E.

Chains

- 80.00 Point for the section cor. of secs. 1, 6, 7, and 12, falls in a wash in the bottom of a draw, where it would be impracticable to perpetuate a cor. monument because of flood waters.
- West, 22 lks. from the true cor. point.
- Set an iron post, 3 ft. long, 2 in. diam., 27 ins. in the ground for the ^{with} cor. of secs. 1, 6, 7, and 12, with the brass cap mkd.
- T15S R70E - R71E
- | | |
|-----|----|
| S1 | S6 |
| S12 | S7 |
- 1934
- raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
- Land, rough mountainous, having a general NW. drainage and exposure.
- Soil, gravelly, clay loam; 3rd rate.
- Timber, pinon, juniper, mahogany and scrub oak.
- Undergrowth, buckbrush, greasewood, manzanita and black sage.
- Grazing, fair.
-
- North, bet. secs. 1 and 6, from true cor. point.
- Over rough mountainous land, through dense undergrowth and scattering timber; descend 50 ft. over a N. slope.
- 2.40 Draw, drains N.; continue to descend slightly along the bottom of the draw.
- 7.70 South edge of draw, (same as above) drains NW; continue to descend 90 ft. along the bottom of the draw.
- 10.40 Wash in the bottom of draw, drains NW.; ascend 40 ft. along the bottom of the draw.
- 12.60 North edge of draw, drains NW.; ascend 60 ft. along a SW. slope.
- 14.90 Point of a spur, projects NW.; continue to ascend 30 ft. over a S. slope.
- 20.30 Spur. projects W.; descend 90 ft. over a N. slope.
- 24.80 Point of a spur, projects from the E.; continue to descend 40 ft. over a N. slope.
- 27.40 Spur, projects W.; continue descent 400 ft. over numerous small spurs, projecting, and draws, draining, W. to the 48.40 ch. point.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground, for the ¼ sec. cor., with the brass cap mkd.