

INDEPENDENT RESURVEY
OF THE RANGE LINE THROUGH T. 13 S., BETWEEN RS. 70 AND 71 E.

Chains	
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the cor. of secs. 1, 6, 7, and 12, with the brass cap mkd.
	T13S
	R70E R71E
	S1 S6
	S7 S12
	1934
	raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.
	Land, rough, broken badlands.
	Soil, sandy clay; 3rd rate.
	Undergrowth, greasewood, creosote and cacti.
	Grazing, poor.
	No timber.
	North, bet. secs. 1 and 6.
	Over broken badlands, across numerous small draws and ravines, through scattering undergrowth.
.70	Ravine, drains W.; heads in a high mesa rim about 6.00 chs. dist.
5.60	Spur, projects approximately 6.00 chs. W.; heads about 4.00 chs. E.
10.00	Ravine, 1.00 ch. wide and 60 ft. deep, drains W. about 2.00 chs., thence SW.; heads about 6.00 chs. E.
13.30	Spur, projects SW. approximately 8.00 chs.
18.00	Ravine, 1.00 chs. wide and 80 ft. deep, drains S. 60° W.
20.40	Fork of a spur, one fork projects W. about 8.00 chs. to a large wash, the other projects N.
26.80	Point of a spur, projecting from the S.
29.80	Ravine, 90 lks. wide and 20 ft. deep, drains W. about 3.00 chs., thence S. 40° W.
33.70	Spur, projects about 8.00 chs. SW. from E.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor., with the brass cap mkd.
	S1 S6
	1934
	raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.
	This cor. falls in the bottom of a small ravine draining S. 70° W.
52.70	Low spur, projects S. 60° W.; continue over numerous small ravines and spurs, draining and projecting S. 60° W.