

INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 13 S., R. 70 E.

Chains	Asc. 60 ft. to 30.30 ch. point.
3.90	Draw, drains S. 80° E.
14.90	Spur, projects E.
17.00	Wash, drains S. 70° E.
19.20	Spur, projects S. 80° E.
30.30	Small spur, projects S. 70° E.; begin ascent along very steep SE. slope of mesa; asc. 410 ft. to 80.40 ch. point.
40.00	On a small bench, Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd. $\begin{array}{c} \frac{1}{4} \\ S2 \mid S1 \\ 1934 \end{array}$ of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. raise a mound
80.00	Point for the lot cor. falls on face of sandstone ledge comprizing rim of mesa and which bears S. 20° W. and N. 10° E.
80.40	Set an iron post, 3 ft. long, 1 in. diam., 14 ins. in the ground and in a large mound of stone for witness cor. lots 5 and 12 of sec. 2, and lots 8 and 9 of sec. 1, with brass cap mkd. $\begin{array}{c} T13SR70E \\ S2 \mid S1 \\ \frac{5}{12} \mid \frac{8}{9} \\ WC \\ 1934 \end{array}$ Asc. 50 ft. along a rolling SE. slope over mesa top.
98.14	Intersect the third standard parallel S. at a point 7.48 chs. W. of the standard cor. secs. 35 and 36, heretofore described. At point of intersection. Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for closing cor. secs. 1 and 2, with brass cap mkd. $\begin{array}{c} T12SR70E \\ S35 \\ S2 \mid S1 \\ T13S \\ CC \\ 1934 \end{array}$ of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, S. of cor. raise a mound Land, broken badlands. Soil, sandy clay; 4th rate. Undergrowth, cacti and greasewood. No timber.