


502

INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 13 S., R. 70 E.

Chains

the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.



of stone, 3 ft. base, $1\frac{1}{2}$ ft. high; W. of cor. raise a mound

Asc. 225 ft.

45.60

Edge of mesa, bears N. 10° E. and S. 10° W.; continue over level mesa top.

79.84

The cor. secs. 2, 3, 10, and 11.

Land, rough in eastern portion, level in western. Soil, sandy clay; 4th rate. Undergrowth, creosote, sagebrush and cacti. No timber.


(X)

N. $0^\circ 01'$ W., on true line bet. secs. 2 and 3.

Asc. over rolling mesa top, through scattering undergrowth.

40.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.



of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. raise a mound

Continue over rolling mesa top.

80.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for cor. of lots 8 and 9, sec. 2 and lots 5 and 12, sec. 3, with brass cap mkd.



Deposit a limestone, 4x4x2 ins., mkd. with a cross (X) at base of post.

97.90

Intersect the third standard parallel south, at a point 7.41 chs. West of the standard cor. of secs. 34 and 35.

At point of intersection,

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for closing cor. of secs. 2 and 3, with brass cap mkd.

