

INDEPENDENT RESURVEY OF THE SUBDIVISIONS OF T. 13 S., R. 70 E.

Chains	Continue over level mesa top.	
43.30	Edge of mesa, bears N. 10° W. and S. 10° E.; desc. 135 ft.	
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for the cor. of lots 8 and 9 of secs. 4 and 5 and 12 of sec. 5, with brass cap mkd.	
	<div style="text-align: center;"> T13SR70E 5 8 S5 — S4 12 9 1934 </div>	
	of stone, 3 ft. base, 1½ ft. high, W. of cor. raise a mound	
	Continue along W. edge of wash.	
87.20	Center of Toguon Wash, drains S. 10° E.; asc. 32 ft. along E. bank of wash.	
95.30	Old road, bears S. 5° E. and N. 10° W.	
98.07	Intersect the third standard parallel, 7.41 chs. W. of the standard cor. of secs. 32 and 33, T. 12 S., R. 70 E. which is an iron post, mkd. and witnessed as described in Book "A", of this group.	
	At the point of intersection,	
	Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground for the closing cor. of secs. 4 and 5, with brass cap mkd.	
	<div style="text-align: center;"> T12SR70E S32 S5 S4 CC T13S 1934 </div>	
	Deposit a basalt stone, 5x3x2 ins. mkd. with a cross (X), at base of post.	
	Land, level to rolling.	
	Soil, sandy clay; 4th rate.	
	Undergrowth, creosote, sagebrush and cacti.	
	No timber.	
	Beginning at the cor. of secs. 5, 6, 31, and 32 on the S. bdy. of the township, which is an iron post, mkd. and witnessed, as described in Book "B" of this groups.	
	Thence	
	N. 0°03' W., bet. secs. 31 and 32.	
	Over gravelly ridges and washes, through scattering undergrowth, desc.	
26.00	Shallow wash, drains SE.; asc. 25 ft.	
30.40	Spur, projects SE.	