

INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 13 S., R. 70 E.

Chains	$\frac{1}{4}$ S6 S5 1934 Deposit a limestone, 9x7x5 ins., mkd. with a cross (X), at base of post. Asc. 10 ft.
55.80	Wash, drains S. 20° W.; asc. 65 ft.
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground for the cor. of lots 8 and 9 of sec. 5 and lots 8 and 15 of sec. 6, with brass cap mkd. TL3SR70E 8 8 S6 —+— S5 15 9 1934 Deposit a limestone, 4x4x2 ins. mkd. with a cross (X), at base of post.
87.50	Wash, drains S. 20° W.
98.30	Intersect the third standard parallel south, 7.41 chs. W. of the standard cor. of secs. 31 and 32, which is an iron post, mkd. and witnessed, as described in Book "A" of this group. At point of intersection. Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, for the closing cor. of secs. 5 and 6, with brass cap mkd. TL2SR70E S31 S6 S5 CC TL3S 1934 of stone, 3 ft. base, 1½ ft. high, S. of cor. raise a mound Land, rolling. Soil, sandy clay; 4th rate. Undergrowth, creosote, sagebrush and cacti. No timber.
7.41	From the standard $\frac{1}{4}$ sec. cor. of sec. 31, described in Book "A", of this group. West. At a point, which is 40.00 chs. W. of the closing cor. of sec. 5 and 6. Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.