

## METES AND BOUNDS SURVEY OF PRIVATE CLAIMS IN T. 13 S., R. 70 E.

Chains					
	T13SR70E				
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 26</td> <td style="padding: 2px;">TR 37</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">AP 3</td> </tr> </table>	S 26	TR 37		AP 3
S 26	TR 37				
	AP 3				
	1934				
	Thence				
	West, bet. tract 37 and public lands.				
	Along old fence line.				
4.00	Leave fence line.				
6.00	Enter river, bank bears N. 60° E. and S. 60° W.				
19.74	In bed of river.				
	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground in concrete for angle point 4/37, with brass cap mkd.				
	T13SR70E				
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 26</td> <td style="padding: 2px;">AP 4</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">TR 37</td> </tr> </table>	S 26	AP 4		TR 37
S 26	AP 4				
	TR 37				
	1934				
	As this cor. is set in river bed and is subject to destruction by seasonal floods, it is desirable to establish a witness cor., therefore:				
	At a point 5.56 chs. North and on the right bank of the river, this being the nearest point at which a permanent monument can be established,				
	Set an iron post, 3 ft. long, 1 in. diam., 24 ins. in the ground, surrounded by a large mound of stone for witness angle point 4/37, with brass cap mkd.				
	T13SR70E				
	<table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 2px;">S 26</td> <td style="padding: 2px;">AP 4</td> </tr> <tr> <td style="padding: 2px;"></td> <td style="padding: 2px;">TR 37</td> </tr> </table>	S 26	AP 4		TR 37
S 26	AP 4				
	TR 37				
	WC 1934				
	Thence, from angle point 4/37.				
	South, bet. tract 37 and public land.				
	Over sand bars of river bottom.				
16.00	Leave river, enter bottom lands; bank bears N. 60° E. and S. 60° W.				
19.37	Angle point 1/39, hereinafter described. Continue bet. tracts 37 and 39.				
39.37	Angle point 4/39 and 3/40, hereinafter described. Continue bet. tracts 37 and 40.				
59.37	Set an iron post, 3 ft. long, 1 in. diam., flush with the ground in concrete for angle point 5/37 and 2/40, with brass cap mkd.				