

5-48 METES AND BOUNDS SURVEY OF PRIVATE CLAIMS IN T. 13 S., R. 70 E.

Chains	North, bet. Tract 45 and public land.
20.20	Angle point 1/45, the place of beginning.
TRACT 48	
Homestead Entry, No. 02195, John L. Pulsipher, entryman, embracing the $\frac{1}{4}$ NE $\frac{1}{4}$, SW $\frac{1}{4}$ NE $\frac{1}{4}$ and SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 24, T. 13 S., R. 70 E. Patented, 160 acres.	
This claim is situated partially in R. 71 E. and partially in R. 70 E. and is surveyed from the same control as that used in the location of Tract 47, in T. 13 S., R. 71 E. and as it is located partially in that township, it was assigned the next higher tract number in that township.	
Control for the location of this entry is taken from the NE. cor. of the claim which is definitely mkd. by an old fence cor., situated in agreement with property lines to the N. and E. and mutually accepted by adjoining landholders. As no lines of culture or improvements furnish satisfactory evidence of the original outboundaries, record courses and distances are followed throughout in establishing the outboundaries.	
Beginning at angle point 1/48, 2/47 and 3/44, described in Book "D", of this group.	
Thence	
West, bet. Tract 48 and public land.	
8.26	From this point the NE. cor. of a concrete house bears S. $33^{\circ}59'$ E., 75 lks. dist.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground for angle point 2/48, with brass cap mkd.
T13SR70E	
S 13 $\left\{ \begin{array}{l} \text{TR 48} \\ \text{AP 2} \end{array} \right.$	
1934	
raise a mound of stone, 3 ft. base, 2 ft. high, SE. of cor.	
From this cor. the $\frac{1}{4}$ sec. cor. of secs. 13 and 24, T. 13 S., R. 70 E. bears S. $79^{\circ}38'$ W., 1.21 chs. dist.	
Thence	
South, bet. Tract 48 and public land.	
20.00	Set an iron post, 3 ft. long, 1 in. diam., 30 ins. in the ground for angle point 3/48, with brass cap mkd.
T13SR70E	
S24 $\left\{ \begin{array}{l} \text{AP 3} \\ \text{TR 48} \end{array} \right.$	
1934	
Thence	