

INDEPENDENT RESURVEY OF THE SUBDIVISION OF T. 13 S., R. 71 E.

Chains	
	Over rough broken badlands.
.10	Enter wash, draining SW.
3.00	Center of wash, drains SW., 50 lks. to junction, meet wash from N.
5.80	Leave wash.
6.70	Set an iron post, 3 ft. long, 2 ins. in diam., 27 ins. in the ground for witness cor. of secs. 5, 6, 7, and 8, with brass cap mkd.
	T13SR71E S6 S5 --- S7 S8 WC 1934
	deposit lime- stone
	6x4x2 ins., mkd. with a cross (x) at base of post.
	Continue over broken flood basin.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.
	$\frac{1}{4}$ S5 S6 1934
	deposit limestone
	8x4x2 ins., mkd. with a cross (x) at base of post.
	Asc. 15 ft.
45.70	Wash, drains S. 70° W., 2 chs. to main wash draining S.
61.00	Wash, drains S. 45° W., 2 chs., to junction of main wash.
66.70	Wash, drains S. 10° W., about 3 chs. to main wash.
70.00	Low spur, 25 ft. above wash, projects S. 80° W.
80.00	Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground for cor. of lots 8 and 15 of sec. 6, and lots 8 and 9 of sec. 5, with brass cap mkd.
	T13SR71E 8 8 S615 9S5 1934
	deposit limestone
	6x6x4 ins., mkd. with a cross (x), at base of post.
	Asc. 70 ft.
97.00	Head of main wash, drains S. 10° W.
97.81	Intersect the Third Standard Parallel South.
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for the closing cor. of secs. 5 and 6, with brass cap mkd.