

## INDEPENDENT RESURVEY OF THE SUBDIVISIONS OF T. 13 S., R. 71 E.

Chain

$$\begin{array}{c} \frac{1}{4} \\ | \\ S4 \quad | \quad S3 \end{array}$$

1934

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

57.40

Wash, drains S. 60° W.; asc. 65 ft.

61.40

Point of spur projecting from N. 60° E.

64.20

Point of spur projecting from N. 60° E.; desc. 80 ft.

66.90

Large wash, drains S. 60° W.; asc. 65 ft.

79.40

Spur, projects S. 30° W.

80.00

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground for cor. of lots 5 and 12 in sec. 4, and lots 7 and 8 in sec. 3, with brass cap mkd.

T13SR71E

$$\begin{array}{c} 5 \quad | \quad 7 \\ S4 \quad | \quad S3 \\ 12 \quad | \quad 8 \\ 1934 \end{array}$$

6x4x3 ins. mkd. with a cross (X) at base of post. deposit limestone,

Continue over broken badlands.

97.77

Intersect the Third Standard Parallel South.

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground for closing cor. of secs. 3 and 4, with brass cap mkd.

T12SR71E

S33

$$\begin{array}{c} S4 \quad | \quad S3 \\ | \\ CC \end{array}$$

T13SR71E

1934

6x4x6 ins., mkd. with a cross (X) at base of post. deposit limestone

From this point the standard cor. of secs. 33 and 34 T. 12 S., R. 71 E. bears East 7.94 chs. dist., an iron post 3 ins. diam., mkd. and witnessed, as described in Book "A" this group.

Land, rolling to broken.

Soil, sandy gravelly clay; 4th rate.

Undergrowth, creosote, sagebrush and cacti.

Timber, none.

ESTABLISHMENT OF ONE QUARTER SECTION CORNERS ON THE 3RD STANDARD PARALLEL SOUTH, REFERRING TO T. 13 S., R. 71 E.

From the standard  $\frac{1}{4}$  sec. cor. of sec. 31, described in Book "A", of this group.

West