

## METES AND MOUNDS SURVEY OF PRIVATE CLAIMS, T. 13 S., R. 71 E.

Chains

Thence

N. 0°16' E., bet. tracts 39 and 40; along old fence and tree line.

20.00

At the NE. to cor. of original sec. 16.

Set an iron post, 3 ft. long, 1 in. diam., flush with the ground in concrete for angle points 3/39, 2/40, 5/41 with brass cap mkd.

T13SR71E

S 17

AP 5 TR 41

AP 3	AP 2
TR 39	TR 40

1934

Thence

S. 89°36' W., bet. tracts 39 and 41; along old brush and wire fence line.

20.02

In an old tree line bearing N. and S., at the CN1/16 cor. of original sec. 17,

Set an iron post, 3 ft. long, 1 in. diam., flush with the ground in concrete for angle point 4/39, 4/41, 1/42, with brass cap mkd.

T13SR71E

S 17

AP 4 TR 41

AP 1	AP 4
TR 42	TR 39

1934

Thence

S. 0°15' E., bet. tracts 39 and 42; along an old tree line.

19.85

Set an iron post, 3 ft. long, 1 in. diam., flush with the ground for witness angle point 5/39 and 5/42, with brass cap mkd.

T13SR71E

S 17

TR 42	AP 5
AP 5	AP 5
TR 39	

WC

1934

20.00

The  $C\frac{1}{4}$  cor. of original sec. 17, which is the true point for angle point 5/39 and 5/42, falls in an irrigating ditch.

Thence from the true point for A. P. 5/39 and 5/42.

S. 89°30' W., bet. tracts 39 and 42; along fence line and irrigating ditch.