

Township 25 South, Range 58 East

The Sixth Standard Parallel South, along the north boundary of the township was surveyed by Brunt and Proctor, Deputy Surveyors, in 1881. The east, west and south boundaries and the subdivision of T. 25 S., R. 58 E. were surveyed by C. A. Magee, Deputy Surveyor, in 1883.

The following field notes are those of a retracement and partial dependent resurvey of a portion of the west boundary and a portion of the subdivision of T. 25 S., R. 58 E.

Reports from private sources alleged that Mineral Survey No. 1921, "Cresstone" Lode, Yellow Pine Mining District, Nevada, was situated in section 32, T. 24 S., R. 58 E. instead of in its officially recorded position in section 30, T. 25 S., R. 58 E. The official plat of Mineral Survey No. 4740, "Akron Fraction" Lode, indicates Survey No. 1921, "Cresstone" Lode to be located in section 31, T. 24 S., R. 58 E.

The present surveys were made incidental to investigation and determination of the actual ground location of Mineral Survey No. 1921, "Cresstone" Lode.

For a description of instrumental equipment used and tests thereof, see field notes entitled "Retracement and Partial Dependent Resurvey of the Sixth Standard Parallel South along a Portion of the South Boundary, and of a Portion of the Subdivision of T. 24 S., R. 58 E.; Incidental to Investigation and Determination of the Actual Ground Location of Mineral Survey No. 1921, "Cresstone" Lode, in the Yellow Pine Mining District, Nevada.

Retracement and Partial Dependent Resurvey of a Portion of the West Boundary, T. 25 S., R. 58 E.

Original Survey Executed by
C. A. Magee, Deputy Surveyor, in 1883.

Note: All items of topography shown in the following field notes were taken from U.S.G.S. Topographic Quadrangle Sheet "Goodsprings", edition of 1919.

Beginning at the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the township, which is monumented with a loosely set limestone, 16x12x10 ins., set in a partially scattered mound of stone and earth and marked with 4 notches on N. edge and 2 notches on S. edge.

I reset the corner stone firmly in the earth and stone mound, and repair and enlarge the surrounding mound of stone.

From this corner, the original $\frac{1}{4}$ sec. cor. of secs. 24 and 25, T. 25 S., R. 57 E., which is monumented with a limestone, 16x14x8 ins., firmly set in an old mound of earth and stone and mkd. $\frac{1}{4}$ on N. face, bears N. $88^{\circ} 33'$ W., 40.37 chs. dist.

I repair and enlarge the surrounding mound of stone.

From the cor. of secs. 19, 24, 25 and 30.

N. $1^{\circ} 02'$ W., bet. secs. 19 and 24.

Along a rolling W. slope.

1.00

Wash, 20 lks. wide, 2 ft. deep, course S. 75° W.; asc. 30 ft. over SW. slope.