

Resurvey of
E. Bdy. of T. 32 N., R. 67 E.

Chains

raise a mound
of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

80.94 Proportionate distance,

Set an iron post, 3 ft. long, 3 ins. diam., 14 ins. in the ground, to bedrock, with a limestone 12x12x6 ins., mkd. X, deposited at base and in a mound of stone to top, for cor. of Ts. 32 and 33 N., R. 67 E., with brass cap mkd.

| | |
|------|------|
| T33N | |
| R67E | T33N |
| S 36 | R68E |
| S 1 | S 31 |
| T32N | |

1939

From this point, the cor. of secs. 13 and 24, on the east boundary of T. 34 N., R. 67 E., bears N. 1° 54' W., 728.86 chs. dist., a limestone, 10x6x8 ins. above ground, mkd. with three grooves on N. face and 3 grooves on S. face.

From the same point, the cor. of secs. 2, 3, 34 and 35 on the N. bdy. of T. 32 N., R. 66 E., bears S. 89° 37' W., 639.50 chs. dist. The position of the original cor., an old post scribed T. 32 N., on S. face, 2 notches on E., and 4 on W., was found by Mr. Carl S. Swanholm, Cadastral Engineer, and remonumented with a two inch iron survey post in 1933, as follows:

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with a rock 3x5x6 ins., mkd. with a cross (X) deposited at the base, and with the old post alongside for the cor. of secs. 2, 3, 34 and 35, with brass cap mkd.

| | |
|------|------|
| T33N | R66E |
| S34 | S35 |
| S 3 | S 2 |
| T32N | |

1933

Land, rolling.
Soil, gravelly; 2nd rate.
Timber, scattering juniper and pinon.
Undergrowth, sagebrush and shadscale.
Grazing, fairly good.

NORTH BOUNDARY OF T. 32 N., R. 68 E.

From the cor. of Ts. 32 and 33 N., Rs. 68 and 69 E.,

West, on a tangent line describing the tangent, bet. secs. 1 and 36, bet. Ts. 32 and 33 N., thru range 68 E. which bears S. 89° 59.2' W.

Asc. 60 ft. over SE. slope.

3.50 Spur, slopes S.; desc. 190 ft. over W. slope.

11.20 Draw, drains S.

15.40 Draw, drains S. 60° E., asc. 330 ft. over E. slope.

30.60 Spur, slopes S.; desc. 130 ft. over NW. slope.