

DEPENDENT RESURVEY SECOND STANDARD PARALLEL NORTH
ALONG THE SOUTH BOUNDARY OF T. 11 N., R. 33 E.

- Chains West, along S. bdy. sec. 32
- 39.83 Find no trace of the closing cor. of secs. 3 and 4, T. 10 N., R. 33 E.
- 140.00 Find no trace of standard cor. of secs. 31 and 32 S. West, on same line, with continuous measurement along S. bdy. sec. 31
- 78.50 Fall 1.10 chs. S. of the standard $\frac{1}{4}$ sec. cor., hereinafter described
- The bearing of this mile therefore is N. $89^{\circ} 12'$ W., and the distance 78.51 chs.
- From the standard $\frac{1}{4}$ sec. cor.
- West, along S. bdy sec. 31
- 39.12 Find no trace of the closing cor. of secs. 4 and 5, T. 10 N., R. 33 E.
- 39.43 Fall 2 lks. S. of the standard cor. of T. 11 N., Rs. 32 and 33 E., hereinafter described
- The bearing of this half mile therefore is N. $89^{\circ} 58'$ W., and the distance 39.43 chs.
- True lines
- The original standard cor. of T. 11 N., Rs. 33 and 34 E. is a trap stone, firmly set in a mound of stone, marked with 6 notches on E. and W. faces.
- Alongside cor.,
- Set an iron post, 3 ft. long, 3 ins. dia., 10 ins. in the ground to solid rock, in a mound of stone, for the standard cor. of T. 11 N., Rs. 33 and 34 E., with brass cap mkd
- | | |
|------|------|
| SC | |
| T11N | |
| R33E | R34E |
| S36 | S31 |
- 1931
- At base of post deposit a mkd(X) trapstone, 10x8x4 ins.
- Thence from the standard cor. of T. 11 N., Rs. 33 and 34 E.
- S. $89^{\circ} 57'$ W., along S. bdy. sec. 36
- Over rough mountainous land through scattering undergrowth