

DEPENDENT RESURVEY SECOND STANDARD PARALLEL NORTH
ALONG THE SOUTH BOUNDARY OF T. 11 N., R. 33 E.

Chains Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the ground, for the closing cor. of secs. 4 and 5, with brass cap mkd

T11NR33E
S 31

S5 S4

CC

T10NR33E
1931

Dig three pits crosswise on line, 18 ins. square, 12 ins. deep, E, S, and W of cor.

63.76 The original standard cor. of T. 11 N., Rs. 32 and 33 E., which is a trap stone, firmly set in the ground, mkd with 6 notches on N, E, and W. faces, alongside which Set an iron post, 3 ft. long, 3 ins. dia., 27 ins. in the ground, for the standard cor. of T. 11 N., Rs. 32 and 33 E., with brass cap mkd

SC
T11N

R32E R33E

S36 S31

1931

Dig three pits crosswise on line, 18 ins. square, 12 ins. deep, N, E, and W. of cor.

Land, mountainous to rolling mountainous.

Soil, rocky with sand, 4th and 3rd rate.

Timber, none.

Undergrowth, sage, squawbrush, rabbit brush.

General drainage, E. 19 chs. N., W. 45 chs. SW.

Grazing, poor.

DEPENDENT RESURVEY EAST BOUNDARY OF T. 11 N., R. 33 E.

REESTABLISHMENT OF SURVEYS EXECUTED BY
CONKLING & STEWART, U. S. DEPUTY SURVEYORS,
UNDER CONTRACT NO. 165, IN 1883

Random lines

From the standard cor. of T. 11 N., R. 33 and 34 E.

North, along E. boundary of township, setting temporary

$\frac{1}{4}$ sec. and sec. cors. at regular intervals of 40.00

and 80.00 chs., without finding any traces of intermediate corners, and at