

SURVEY OF PORTION OF S. BOUNDARY T. 8 N., R. 46 E.

Chains							
44.34	Westing of 40.00 chs. from the cor. of T. 8 N., Rs. 46 and 47 E., hereinafter described Set an iron post, 3 ft. long, 1 in. dia., 27 ins. in the ground, for the $\frac{1}{4}$ sec. cor. of sec. 36 only, with brass cap mkd $\frac{1}{4}$ S36 1931 From which A pinon, 8 ins. dia., bears N. $57\frac{1}{2}^{\circ}$ E., 80 lks. dist., mkd $\frac{1}{4}$ S36BT A pinon, 6 ins. dia., bears N. $45-3/4^{\circ}$ W., 60 lks. dist., mkd $\frac{1}{4}$ S36BT						
44.75	Bottom of small draw, drains N. Asc. 75 ft. to						
50.30	Top of rocky spur, projects N. Desc. 40 ft. to						
52.25	Draw, drains N. Asc. steep NW. slope 80 ft. to						
60.15	In saddle of large spur, projects N. Desc. steep SE. slope						
73.00	Desc. along steep rocky S. slope						
77.30	Rocky outcropping, 190 ft. below saddle Desc. abrupt rocky broken E. slope 290 ft. to						
84.34	At a point directly south of the cor. of Ts. 8 and 9 N., Rs. 46 and 47 E., hereinafter described Set an iron post, 3 ft. long, 3 ins. dia., 27 ins. in the ground, for the cor. of T. 8 N., Rs. 46 and 47 E., with brass cap mkd <table><tr><td>T8N</td><td>R46E</td><td>R47E</td></tr><tr><td>S36</td><td>S31</td><td></td></tr></table> 1931 From which	T8N	R46E	R47E	S36	S31	
T8N	R46E	R47E					
S36	S31						