

SURVEY OF PORTION OF S. BOUNDARY T. 8 N., R. 46 E.

Chains A pinon, 8 ins. dia., bears N. $51\frac{1}{4}^{\circ}$ E., 63 lks. dist.,
 mkd T8NR47ES31BT
 A pinon, 8 ins. dia., bears S. $18-3/4^{\circ}$ E., 58 lks. dist.,
 mkd T7NR47ESBT
 A pinon, 14 ins. dia., bears N. $55\frac{1}{4}^{\circ}$ W., 31 lks. dist.,
 mkd T8NR46ES36BT
 Cor. stands on steep E. slope in heavy timber.
 Land, rough mountainous. Soil, sandy and gravelly, with
 much surface and slide rock, 4th rate.
 Timber, pinon, juniper; mt. mahogany on ridges.
 Undergrowth, sagebrush, bunch grass, yellow top, buckbrush.
 General drainage, N. Grazing, fair.

DEPENDENT RESURVEY OF PORTION OF N. BOUNDARY T. 8 N., R. 46 E.

REESTABLISHMENT OF SURVEYS EXECUTED BY DON H. BARKER,
 U. S. DEPUTY SURVEYOR IN 1874

Random lines

From the cor. of secs. 1, 2, 35, and 36, on N. bdy. of
 T. 8 N., R. 46 E., hereinafter described
 East, bet. secs. 1 and 36
 39.28 Fall 62 lks. N. of the original $\frac{1}{4}$ sec. cor., hereinafter
 described
 The bearing of this half mile is S. $89^{\circ} 06'$ E., and the
 dist., 39.28 chs.
 From the $\frac{1}{4}$ sec. cor.
 East, with continuous measurement
 78.82 Fall 67 lks. N. of the original cor. of Ts. 8 and 9 N.,
 Rs. 46 and 47 E., hereinafter described
 The bearing of this half mile is S. $89^{\circ} 02'$ E., and the
 dist., 39.54 chs.

True lines

The original cor. of secs. 1, 2, 35, and 36, on N. bdy.
 of T. 8 N., R. 46 E., is a basalt stone, 6X8X12 ins.,
 firmly set in the ground, mkd with 1 notch on E. and 5
 notches on W. faces, along side which
 Set an iron post, 3 ft. long, 2 ins. dia., 27 ins. in the