

## DEPENDENT RESURVEY OF PORTION OF N. BOUNDARY T. 8 N., R. 46 E.

Chains

T9N	
R46E	R47E
S36	S31
S1	S6
T8N	
1931	

Raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, S. of cor.

Chimney of Combination Mill, bears N.  $78^{\circ} 01'$  W.  
Center Line of old Eldorado Mill Building, bears N.  $83^{\circ} 21'$  W.  
Stone Cabin (about 8 miles distant), bears N.  $21^{\circ} 53'$  W.  
Ruins of old chimney at cabin, bears S.  $21^{\circ} 52'$  W., about 32 chs.

Land, gently rolling. Soil, sandy and gravelly to rocky clay loam, 3rd rate. Timber, few scattering juniper. Undergrowth, yellow top, sagebrush, shadscale, willow. General drainage, NW. Grazing, poor.

## DEPENDENT RESURVEY OF PORTION OF W. BOUNDARY T. 8 N., R. 46 E.

REESTABLISHMENT OF SURVEYS EXECUTED BY DON H. BARKER,  
U. S. DEPUTY SURVEYOR IN 1874

Random lines

From the cor. of Ts. 8 and 9 N., Rs. 45 and 46 E.,

hereinafter described

South, bet. secs. 1 and 6

39.75 Fall 40 lks. E. of the original  $\frac{1}{4}$  sec. cor., hereinafter described

The bearing of this half mile is S.  $0^{\circ} 34'$  W., and the dist. 39.75 chs.

From the  $\frac{1}{4}$  sec. cor.

South, with continuous measurement

78.79 Fall 90 lks. E. of the original cor. of secs. 1, 6, 7, and 12, hereinafter described

The bearing of this half mile is S.  $1^{\circ} 19'$  W., and the dist. 39.05 chs.

True lines

The original cor. of Ts. 8 and 9 N., Rs. 45 and 46 E.,

is a granite stone, 5X12X14 ins., firmly set in the ground, mkd with 6 notches on N, E, S, and W. faces

Alongside original cor.

Set an iron post, 3 ft. long, 3 ins. dia., 27 ins. in the ground, for the cor. of Ts. 8 and 9 N., Rs. 45 and