

222

Subdivision of T 8 N, R 48 E.

Chains

Beginning at the corner of sections 1, 2, 35, and 36 on the south boundary of the township, heretofore described, thence:

N 0°01' W, between sections 35 and 36.

Over mountainous land, through scattering pinon and juniper timber and a scant undergrowth of sagebrush, weeds and grass, descend 5 ft, along a NE slope

.80 Draw, drains N 80° E, ascend 210 ft. along a SE slope.

6.60 Spur, projects E, descend 120 ft. along a NE slope.

10.90 Draw, drains E, ascend 150 ft. along a S slope.

12.90 Spur, projects SE, descend 15 ft. along a NE slope.

19.40 Small draw, drains N 80° E, ascend 30 ft. along a SE slope

40.00 On top of a broad ridge bearing N 60° E and S 60° W:

Set an iron post, 3 ft. long and 1 in. in diameter, 14 ins. in the ground to solid rock and in a mound of stone for the $\frac{1}{4}$ section corner, with brass cap marked:

$$\begin{array}{c} \frac{1}{4} \\ \text{S35} \mid \text{S36} \\ 1932 \end{array}$$

whence

A pinon, 14 ins. in diameter, marked $\frac{1}{4}$ S36BT, bears N 87°45' E, 126 lks. distant.

A pinon, 14 ins. in diameter, marked $\frac{1}{4}$ S35BT, bears S 51°15' W, 242 lks. distant.

Descend 60 ft. along a NW slope.

48.00 Small seep in the head of a draw draining NW, ascend 35 ft. along a SW slope.

53.00 Spur, projects W, descend 135 ft. along a N slope.

80.00 On a rocky N slope:

Set an iron post, 3 ft. long and 2 ins. in diameter, 10 ins. in a hole drilled into solid rock and in a mound of stone, for the corner of sections 25, 26, 35, and 36, with brass cap marked:

$$\begin{array}{c} \text{T8N R48E} \\ \text{S26} \mid \text{S25} \\ \text{S35} \mid \text{S36} \\ 1932 \end{array}$$

whence

A pinon, 9 ins. in diameter, marked T8NR48ES25BT, bears N 28°30' E, 128 lks. distant.

A pinon, 3 ins. in diameter, marked 'BT' only, bears N 21°15' W, 66 lks. distant.

A pinon, 10 ins. in diameter, marked T8NR48ES36BT, bears S 68°00' E, 164 lks. distant.