

METHOD OF PROCEDURE

The special instructions for surveys under Group No. 174, Nevada, dated March 8, 1933 and approved by letter 1462595 "E" WSW dated July 27, 1933, provided for the retracement and resurvey of the old boundaries, the completion of the survey of the new boundaries and the survey of the subdivision of T. 22 N., R. 54 E., on the theory that the early surveys were fairly regular and that suitable control could be readily developed. Extended retracements of official adjacent surveys developed the fact that, due to fictitious surveys and gross irregularities, the range line in T. 22 N., between Rs. 53 and 54 E., would not provide suitable control. Supplemental special instructions in the form of a letter dated March 17, 1936 based upon a report of survey conditions submitted by Robert C. Yundt, Surveyor, dated February 4, 1936 as modified in letter of approval, 142595 "E" WSW dated May 26, 1936, provided for the dependent resurvey of the W. bdy. of T. 22 N., R. 54 E., with corners at record distance in latitude counting from the NW. cor. of T. 22 N., R. 54 E., and on true line between the above tp. cor. and the cor. of T. 21 N., Rs. 53 and 54 E., which was reestablished in 1933 under Group No. 133. Fractional T. 21½ N. R. 54 E., was created under the foregoing procedure, the N. bdy. of which is established by running East on true line to an intersection with a line run North from the cor. of Ts. 21 and 21½ N., Rs. 54 and 55 E., the latter corner being established at a point 160.00 chs. east of the original cor. of secs. 2, 3, 34 and 35 on north boundary of T. 21 N., R. 54 E.

Chains

DEPENDENT RESURVEY OF WEST BDY. OF T. 22 N., R. 54 E.

REESTABLISHMENT OF THE SURVEYS EXECUTED BY
BRIDGES AND EATON, DEPUTY SURVEYORS IN 1879
UNDER CONTRACT NO. 88

The lines of the original survey were retraced, and search made for evidence of original corners. The true line notes only are given herein.

Beginning at the cor. of Tps. 22 and 23 N., Rs. 53 and 54 E., which is marked by a surfaced juniper stake, 24"x2"x2", lying on a low, eroded mound of earth. The cor. monument has distinct scribe marks on each face.

At point for cor.,

Set an iron post, 3 ft. long, 3 ins. diam., 30 ins. in the ground with the marked stake deposited at the base, for cor. of Tps. 22 and 23 N., Rs. 53 and 54 E., with brass cap mkd.

T23N

R53E R54E

S36 | S31

S1 | S6

T22N

1936