DEPENDENT RESURVEY FIFTH STANDARD PARALLEL SOUTH, THROUGH RANGE 63 EAST.

On the secant, Set am iron post, 3 ft. long, 2 ins. in dia., 20 ins. in the ground on solid rock and supported by a mound of stone for standard cor. of secs. 35 and 36, with brass cap marked SC T203 R63E S35 S36 1931 Land, low, rolling and broken mountains. Soil, gravelly, rocky, and dry clay; 3rd, and 4th. rates. No timber. Undergrowth, creosote and chaparral. East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears S.69°58.7°E: Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE; ascend 120 ft. over rocky w. slope. Difference bet. measurement of 40.00 chs. by two sets of chaimmen, is 1 lk.; position of middle point. By lst. set, 40.005 chs. By 2nd. set, 33.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set am iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard sec. cor., with brass cap marked 1931	Chains	er La	10
Set an iron post, 3 ft. long, 2 ins. in dia., 20 ins. in the ground on solid rock and supported by a mound of stone for standard cor. of sees. 35 and 36, with brass cap marked T208	80.00	Land, mountainous.	
1931 Limestone, 8x6x4 ins., marked with a cross (+) on one face at base of monument. Land, low, rolling and broken mountains. Soil, gravelly, rocky, and dry clay; 3rd. and 4th. rates. No timber. Undergrowth, creosote and chaparral. East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears \$.89°58.77 c. Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE.; ascend 120 ft. over rocky w. slope. 23.65 Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point. By lst. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard \$ sec. cor., with brass cap marked 1931 Leave hills or rolling and broken ground, enter table	Charles of the Charle	Set an iron post, 3 ft. long, 2 ins. in dia., 20 ins. the ground on solid rock and supported by a mound of stone for standard cor. of secs. 35 and 36, with brass	
limestone, 8x6x4 ins., marked with a cross (+) on one face at base of monument. Land, low, rolling and broken mountains. Soil, gravelly, rocky, and dry clay; 3rd, and 4th. rates. No timber. Undergrowth, creosote and chaparral. East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears \$1.89 \cdot 88.7\frac{1}{12}. Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE.; ascend 120 ft. over rocky W. slope. 23.65 Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point— By 1st. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard \$ sec. cor., with brass cap marked 1931 deposit a limestone, 6x6x4 ins., marked with a cross (+) on one face at base of monument; also, raise a mound of stone, 3 ft.base, 2 ft.high, N. of cor.	Among the head of the contract of	T20S R63E S35 S36	
limestone, 8x6x4 ins., marked with a cross (+) on one face at base of monument. Land, low, rolling and broken mountains. Soil, gravelly, rocky, and dry clay; 3rd. and 4th. rates. No timber. Undergrowth, creosote and chaparral. East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears \$1.89 \cdot 8.7\ff. Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, l ch. wide, drains SE.; ascend 120 ft. over rocky W. slope. Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point. By 1st. set, 40.005 chs. By 2nd. set, 39.995 ohs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 1 sec. cor., with brass cap marked 1931 1931 1931 1 limestone, 6x6x4 ins., marked with a cross (+) on one face at base of monument; also, raise a mound of stone, 3 ft. base, 2 ft.high, N. of cor. Leave hills or rolling and broken ground, enter table	Mise	1931 Rest, along the following the secent, which he are 25, on a transit a transferent the secent, which he are 2.89 88.4 E.	
Soil, gravelly, rocky, and dry clay; 3rd. and 4th. rates. No timber. Undergrowth, creosote and chaparral. East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears \$.89°58.7°E: Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE.; ascend 120 ft. over rocky W. slope. 23.65 Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point— By 1st. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard \$ sec. cor., with brass cap marked 1931 1931 1931 1931 Leave hills or rolling and broken ground, enter table	113/2011	limestone, 8x6x4 ins., marked with a cross (+) on one face at base of monument.	
Soil, gravelly, rocky, and dry clay; 3rd. and 4th. rates. No timber. Undergrowth, creosote and chaparral. East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears S.89°58.7°E: Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE; ascend 120 ft. over rocky W. slope. Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point. By lst. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in. dia., 28 ins. in the ground for standard 1 sec. cor., with brass cap marked 1931 10 1931 11 10 1931 12 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	# 13	Land, low, rolling and broken mountains.	31
Undergrowth, creosote and chaparral. East; along the S. bdy. of sec. 36, on a transit line describing the secant, which bears S.89°58.7°E: Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE.; ascend 120 ft. over rocky W. slope. 23.65 Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point— By 1st. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard \$ sec. cor., with brass cap marked 1931 1931 1931 1 Set an iron post, 3 ft. long, 2 in. in dia., 28 ins. in the ground for standard \$ sec. cor., with brass cap marked 1931 1931 1931 1931 Leave hills or rolling and broken ground, enter table			es.
East; along the S. bdy. of sec. 36, on a transit line describing the secant, which bears S.59°58.7 %: Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE.; ascend 120 ft. over rocky W. slope. 23.65 Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point. By 1st. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard f sec. cor., with brass cap marked 1931 1931 1036 1931 1037 1038 1	≥¢ e)16	No: timber vois . Fi 65 . At adv and race to inio? 68.	8I
describing the secant, which bears \$.89°58.7 %: Over rolling and broken ground through creosote and chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE.; ascend 120 ft. over rocky W. slope. 23.65 Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point. By 1st. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard \$ sec. cor., with brass cap marked 1931 10 1931 10 21 22 23 24 25 25 25 25 25 25 25 25 25 25 25 25 25	nă su		ES.
chaparral undergrowth. 1.50 Wash, 1 ch. wide, drains SE.; ascend 120 ft. over rocky W. slope. 23.65 Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point— By 1st. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard \$ sec. cor., with brass cap marked Sc. SC. SC. Sc. St. St. St. St. St. St. St. St. St. St	90 • 3	East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears S.89°58.7 E:	35
Top of knoll, bears N. and S.; descend 140 ft. over E. slope. Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point. By lst. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 1 sec. cor., with brass cap marked 1931	in aise	Over rolling and broken ground through creosote and chaparral undergrowth.	
Difference bet. measurement of 40.00 chs. by two sets of chainmen, is 1 lk.; position of middle point. By 1st. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 1 sec. cor., with brass cap marked Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 1 sec. cor., with brass cap marked 10.00	1.50	Wash, 1 ch. wide, drains SE.; ascend 120 ft. over rock. W. slope.	У
By 1st. set, 40.005 chs. By 2nd. set, 39.995 chs.; the mean of which is 40.00 N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 1 sec. cor., with brass cap marked 10.00 10	111 . 311	Difference bet. measurement of 40.00 chs. by two sets	
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 4 sec. cor., with brass cap marked Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 4 sec. cor., with brass cap marked Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 4 sec. cor., with brass cap marked Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 4 sec. cor., with brass cap Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 28 ins. in Set an iron post, 3 ft. long, 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in Set an iron post, 2 in dia. Set an iro		By 1st. set, 40.005 chs.	
Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 1 sec. cor., with brass cap marked . To be a sec of the abusta . To be abusta	Committee and a second committee of		
bnooss villaulary : 3 entire, entire and a strong days of the store of the store, face at base of monument; also, raise a mound of store, 3 ft.base, 2 ft.high, N. of cores, the store of t	ano n	Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard & sec. cor., with brass cap	n
1931 10 at a limestone, 6x6x4 ins., marked with a cross (+) on one face at base of monument; also, raise a mound of stone, 3 ft.base, 2 ft.high, N. of core, the start value of the base of monument and broken ground, enter table	;	Cor. stands on tog or 32 low, proad spur projecting descend 25 rt. over 362 4pc.	
face at base of monument; also, raise a mound of stone, 3 ft.base, 2 ft.high, N. of core that yate and broken ground, enter table		over rolling and broken group.	2.6
Leave hills or rolling and broken ground, enter table or bench lands, bears NE. and SW.	To ets	face at base of monument; also, raise a mound of stone 3 ft.base, 2 ft.high, N. of core does not be stone	,
	63.70	Leave hills or rolling and broken ground, enter table or bench lands, bears NE. and SW.	