

DEPENDENT RESURVEY
FIFTH STANDARD PARALLEL SOUTH, THROUGH RANGE 64 EAST.


Chains

By 1st. set, 80.005 chs.
By 2nd. set, 79.995 chs.; position of middle point

80.00

On the secant,

Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for standard cor. of secs. 35 and 36, with brass cap marked



1931

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

From this cor., U. S. Coast and Geodetic Survey triangulation point on Black Mt., bears S.41°39'W., mound of stone on gypsum mountain butte, bears S.84°49'W.; mound of stone on Sunrise Mt., bears N.83°06'W., and sharp peak on Wilson Mt. in Arizona, bears S.42°25'E.

Land, rolling and broken flood plain; drainage S.

Soil, gravelly, rocky, and dry clay loam; 3rd. rate.

No timber.

Undergrowth, creosote and chaparral.

East, along the S. bdy. of sec. 36, on a transit line describing the secant, which bears S.89°58.7'E.

Over rolling land, through creosote and chaparral undergrowth.

27.90


Wash, 1 ch. wide, drains S.

Difference bet. measurement of 40.00 chs. by two sets of chainmen is nothing:

40.00

N. 2 lks. from the secant,

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard 1/4 sec. cor., with brass cap marked



1931

raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

56.75

Low rocky spur, projects S.30°E.; descend 100 ft. to

66.90

Wash, 1 1/2 chs. wide, drains S.30°W.; ascend rocky W. slope.

Difference bet. measurement of 80.00 chs. by two sets of chainmen, is 4 lks.; position of middle point-