

DEPENDENT RESURVEY
 FIFTH STANDARD PARALLEL SOUTH, THROUGH RANGE 65 EAST.

Chains	
	some clay on W. portion; 4th. rate. No timber.
	Undergrowth, scattered creosote brush.
	East, along the S. bdy. of sec. 36, on a transit line describing the secant which bears S.89°58.7'E.
	Ascend steep, rocky, general W. slope over rough mountainous land, through scattered creosote undergrowth; considerable area of barren surface rock.
8.20	Rocky spur, 225 ft. above sec. cor., projects S.30°W. about 5 chs. distant to end; thence along general S. slope, ascending.
14.10	Draw, drains SW. for about 5 chs., thence W. for about 10 chs., then SW.
21.50	High, rocky spur, 170 ft. above last spur, projects S.20°W.; descend SE. slope 130 ft. to
29.10	Rocky draw, drains SW.; ascend abruptly SW. slope.
36.90	Rocky point, 130 ft. above draw, projects S.; descend.
40.00	N. 2 lks. from the secant, Set an iron post, 3 ft. long, 1 in. in dia., 18 ins. in the ground on solid rock and supported by a mound of stone for standard $\frac{1}{4}$ sec. cor., with brass cap marked
	SC $\frac{1}{4}$ S 36
	1931
	deposit a volcanic rock, 10x6x6 ins. marked with a cross (+) on one face at base of post.
	Cor. stands on steep, rocky SE. slope, 30 ft. below point; continue descent.
43.00	Draw, near head, 25 ft. below $\frac{1}{4}$ sec. cor., drains S.10°E.; ascend 40 ft. to
48.40	High, rocky ridge, bears N.30°W. and S.20°E.; descend steep E. and NE. slopes.
52.40	Draw, heads about 5 chs. distant to the SW. and drains NE. for about 5 chs., thence S.70°E., 165 ft. below ridge; ascend abruptly over rocky NW. slope 90 ft. to
57.20	Rocky point on N. slope; descend broken N. and E. slopes over cliffs and bedrock.
67.70	Canyon, 385 ft. below point, drains S.70°E.; thence along S. slope.