

DEPENDENT RESURVEY

T24 S SIXTH STANDARD PARALLEL SOUTH, THROUGH RANGE 62 EAST.

Chains

Difference bet. measurement of 80.00 chs. by two sets of chainmen is nothing:

80.00 N. 18 lks. from the tangent, a

Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for standard cor. of secs. 35 and 36, with brass cap marked

S C	
T24S	R62E
S35	S36

1931

raise a mound of stone, 3 ft. base, 2½ ft. high, N. of cor.

Land, nearly level; drains NE.

Soil, sandy clay loam and gravelly; 2nd. rate.

No timber.

Undergrowth, dense creosote and chaparral.

East, along the S. bdy. of sec. 36, on a transit line describing the tangent S. of sec. 36 and which bears S. 89° 56.9' E.

Over level land through dense creosote and chaparral undergrowth.

Difference bet. measurement of 40.00 chs. by two sets of chainmen is nothing:

40.00 N. 22 lks. from the tangent,

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for standard ¼ sec. cor., with brass cap marked

SC	
¼ S 36	

1931

raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.

Difference bet. measurement of 80.00 chs. by two sets of chainmen is nothing:

80.00 N. 26 lks. from the tangent,

Set an iron post, 3 ft. long, 3 ins. in dia., 28 ins. in the ground for standard cor. of T. 24 S., Rs. 62 and 63 E., with brass cap marked

SC	
T24S	
R62E	R63E
S36	S31

1931