

DEPENDENT RESURVEY

SIXTH STANDARD PARALLEL SOUTH, THROUGH RANGE 64 EAST.

Chains					
	East, along the S. bdy. of sec. 36, on a transit line describing the tangent S. of sec. 36 and which bears S.89°56.9'E.				
	Descend rocky NE. slope over rolling and broken land through creosote undergrowth.				
3.90	Draw, 25 ft. below sec. cor., drains N.30°W.				
8.00	Spur, projects N.				
16.95	Wash, drains N.20°W.; gradually ascend.				
32.00	Rocky spur, projects N.30°W.; gradually descend.				
40.00	N. 22 lks. from the tangent, Set an iron post, 3 ft. long, 1 1/2 ins. in dia., 30 ins. in the ground for standard 1/4 sec. cor., with brass cap marked				
	<p>SC 1/4 S 36</p> <hr/> <p>1931</p> <p style="text-align: right;">raise a</p> <p>mound of stone, 3 ft. base, 2 1/2 ft. high, N. of cor.</p> <p>Cor. stands in a wide, shallow wash draining N.20°W.</p>				
48.00	Begin ascent over rocky W. slope.				
63.60	Rocky spur, 150 ft. above 1/4 sec. cor., projects N.20°W.; gradually descend.				
67.60	Draw, drains N.20°W.; ascend rocky NW. slope 165 ft. to Tp cor.				
71.60	Spur, projects N.55°W.				
74.00	Wash, drains N.60°W.				
80.00	N. 26 lks. from the tangent, Set an iron post, 3 ft. long, 3 ins. in dia., 14 ins. in the ground on solid rock and supported by a large mound of stone for standard cor. of T.24 S., Rs. 64 and 65 E., with brass cap marked				
	<p>SC T24S</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td>R64E</td> <td>R65E</td> </tr> <tr> <td>S36</td> <td>S31</td> </tr> </table> <hr/> <p>1931</p> <p>Cor. stands on ridge, bears NW. and SE.</p> <p>Land, rolling and broken; general NW. exposure and drainage.</p> <p>Soil, gravelly and rocky; 4th. rate.</p> <p>No timber.</p> <p>Undergrowth, creosote.</p>	R64E	R65E	S36	S31
R64E	R65E				
S36	S31				