

DEPENDENT RESURVEY NORTH BOUNDARY OF T.22 S., R.63 E.

Chains

True Lines.

The cor. of Tps. 21 and 22 S., Rs. 62 and 63 E., is a basalt rock, 7x7x7 ins. above ground, firmly set in the center of an old deeply embedded mound of stone and marked with 6 notches on N., S., E., and W. edges.

At cor. point,

Set an iron post, 3 ft. long, 3 ins. in dia., 28 ins. in the ground in the center of an embedded automobile tire rim and with the original cor. monument buried alongside for cor. of Tps. 21 and 22 S., Rs. 62 and 63 E., with brass cap marked

T21S
R62E | R63E
S36 | S31

S1 | S6

T22S

1931

raise a mound of stone, 4 ft. base, 3 ft. high, S. of cor.

Note: The original corner monuments along the N. bdy. of T.22 S., R.63 E. will be defective in position with reference to the new subdivisional surveys in that Tp., therefore, in the remonumentation of the corners along the bdy., they are marked to refer to secs. in T.21 S., R. 63 E. only.

Thence

S.89°49'E., along the S. bdy. of sec. 31, T.21 S., R.63 E.

Over gently rolling flood plain, through a medium growth of creosote and cacti undergrowth; gradually ascend gentle W. slope.

40.72 The $\frac{1}{4}$ sec. cor. which is a basalt stone, 14x10x8 ins., firmly set in the center of an old deeply embedded mound of stone, and marked $\frac{1}{4}$ on N. face.

At cor. point,

Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground with original cor. monument buried alongside for $\frac{1}{4}$ sec. cor. S. bdy. sec. 31, T.21 S., R.63 E., with brass cap marked

$\frac{1}{4}$ S31

1931

raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.

Thence

N.89°42'E., with continuous measurement.

60.10 Old road, bears NE. and SW.

81.62 The cor. of secs. 5, 6, 31, and 32, which is a basalt stone, 16x10x7 ins., firmly set in a mound of stone, and marked with 5 notches on E. and 1 notch on W. edge.

At cor. point,