

DEPENDENT RESURVEY WEST BOUNDARY OF T.22 S.,R.63 E

Chains

the ground for $\frac{1}{4}$ sec. cor. E. bdy. sec. 1, T.22 S.,R.62 E., with brass cap marked

$\frac{1}{4}$
SI

1931

raise a mound of stone, 3 ft.base, 2 ft.high, W. of cor.

Thence

N.0°19'E., with continuous measurement.

40.15 Graded dirt road, bears E. to junction with the Las Vegas-Searchlight road and W. to buildings at "Jerico Heights Subdivision" about 60 chs. distant.

58.80 Graded dirt road, bears N.35°W. to Las Vegas and S.35°E. to Boulder City and Searchlight, Nevada.

70.86 Telephone line, (10 wires) bears N.56°07'W. and S.56°07' E. to Boulder City, Nev.

80.19 The reconstructed original cor. of Tps. 21 and 22 S., Rs. 62 and 63 E. heretofore described.

Land, nearly level gravelly flood plain.

Soil, coarse sandy loam and gravelly; 3rd. to 4th.rates.

No timber.

Undergrowth, creosote, cacti, and sagebrush.


DEPENDENT RESURVEY WEST BOUNDARY OF T.23 S.,R.63 E.

REESTABLISHMENT OF SURVEYS EXECUTED BY
T. A. MAGEE, U. S. DEPUTY SURVEYOR
IN 1883.

In order to restore the cor. of Tps. 23 and 24 S.,Rs. 62 and 63 E., I begin at the cor. of Tps. 23 and 24 S., Rs. 61 and 62 E., which is a basalt stone, 24x11x8 ins., firmly set in a mound of stone, and marked with 6 notches on N., S.,E., and W. faces.

At cor. point,

Set an iron post, 3 ft. long, 3 ins. in dia., 27 ins. in the ground and bury original cor. monument, alongside for cor. of Tps. 23 and 24 S., Rs. 61 and 62 E., with brass cap marked



1931

raise a mound of stone, 5 ft.base, 5 ft.high, S. of cor.