Chains

INDEPENDENT RESURVEY, SUPERSEDING SURVEY
EXECUTED BY T.A.MAGEE, U.S.DEPUTY
SURVEYOR IN 1883.

From the cor. of T.23 S.,Rs. 63½ and 64 E., heretofore described.

North, bet. secs. 31 and 36.

Over rolling valley draining W., through creosote and chaparral undergrowth.

17.00 Broad shallow wash, drains N.70°W.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for ¼ sec. cor., with brass cap marked

¼
S36 | S31
1931

raise a mound of stone, 3 ft.base, 2 ft.high, W. of cor.

80.00 Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for cor. of secs. 25,30,31, and 36, with brass cap marked

T23S
R63½E | R64E
S25 | S30
S36 | S31
1931

raise a mound of stone, 3 ft.base, 3 ft.high, W. of cor.

Land, nearly level valley; general W. exposure and drainage.

Soil, coarse sandy and gravelly loams; 2nd. rate.

No timber.

Undergrowth, creosote and chaparral.

---

North, bet. secs. 25 and 30.

Over gently rolling sandy land draining W. and SW., through creosote and chaparral undergrowth.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for ¼ sec. cor., with brass cap marked

¼
S25 | S30
1931

raise a mound of stone, 3 ft.base, 2½ ft.high, W. of cor.