e.5772	
	, INDEPENDENT RESURVEY WEST BOUNDARY OF T.23 S., R.64 E.
Chains	· · · · · · · · · · · · · · · · · · ·
07 . 10	North, bett secs hand 6. about) gawagin spend of TP. and bloves , grif is should be the control of the control
	Ascend over rolling and broken mountainous land through creosote and chaparral undergrowth.
6.00	Spur, 50 ft. above sec. cor., projects S.10°W.; continue ascent over W. and SW. slopes.
19.96	Intersect Boulder Canyon Projects Federal Reservation Boundary.
. 290	Set an iron post, 3 ft. long, 2 ins. in dia., 28 ins. in the ground for closing cor. of secs. 1 and 6, with brass cap marked
ul .vil	oh , sin ni . si I , T23S , ser certi so fed the real control R63½E R64E a ser certi so ser certi S1 S6 C C
	BCPFR 1931
5 9	mound of stone, 4 ft. base, 3 ft.high, N. of cor.
· The same	From this cor., the 16th. Mile Cor. of the reservation boundary, bears West, 18.02 chs. distant; an iron post, 3 ins. in dia., firmly set, and marked and witnessed as described in the official record.
40.00	On SW. slope near top of spur projecting SE., 210 ft. above sec. cor.
Dayn a	Set an iron post, 3 ft. long, 1 in. in dia., 28 ins. in the ground for 4 sec. cor., with brass cap marked
	4
	S1 - S6
	1931
	mound of stone, 3 ft.base, 3 ft.high, W. of cor.
	Ascend 20 ft. to
41.25	Spur, projects SE.; gradually descend.
44.67	Draw, drains SE.; gradually ascend.
49.10	Begin ascent over abrupt S. slope.
57.35 - south re	Junction of spurs projecting SW. and SE. from N.10°W., 300 ft. above draw; descend 70 ft. to
62.75	Head of draw, drains E.; ascend 310 ft. over broken SE. slope over numerous outcrops and Ledges.
79.10	Rocky ridge, bears W., E. about 2 chs., then NE. and SE.; descend.
80.00	On NW. slope 20 ft. below ridge.
	Set an iron post, 3 ft. long, 3 ins. in dia., 6 ins. in