

INDEPENDENT RESURVEY NORTH BOUNDARY OF T.23 S., R.63½ E.

Chains

INDEPENDENT RESURVEY SUPERSEDING SURVEY EXECUTED
BY T. A. MAGEE, U. S. DEPUTY SURVEYOR
IN 1883.

From the cor. of Tps. 22 and 23 S., Rs. 63½ and 64 E.,
heretofore described.

West, bet. secs. 1 and 36.

Along rocky N. slope over rough mountainous land through
creosote and chaparral undergrowth; ascend 95 ft. to
spur.

2.00 Head of draw, drains NW.

8.25 Ridge spur, bears NW. and S.20°E.; descend rocky SW.
slope.

20.90 Head of draw, 265 ft. below ridge spur, drains SE.;
ascend 130 ft. along steep S. slope.

24.30 Ridge spur, bears NE., SW. for about 5 chs., then S.;
descend steep and rocky NW. slope 340 ft. to draw.

31.70 Rocky spur, slopes N.75°W.; descend W. slope.

38.60 Rocky draw, drains SW.; ascend broken S. slope 40 ft.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 10 ins. in
the ground over a cross (+) cut in bedrock and supported
by a large mound of stone for ¼ sec. cor., with brass
cap marked

S36

¼

S1

1931

Cor. stands on a rocky SW. slope.

47.20 Intersect E. bdy. sec. 36, T.22 S., R.63 E.

Set an iron post, 3 ft. long, 3 ins. in dia., 6 ins. in
the ground on solid rock and supported by a large mound
of stone for closing cor. of Tps. 22 and 23 S., R.63½ E.,
with brass cap marked

T22S

R63E | R63½E

S36

S36

S1

T23S

1931

deposit a

basalt stone, 6x5x4 ins., marked with a cross (+) on one
face at base of post.

From this cor., the ¼ sec. cor. E. bdy. sec. 36, T.22 S.,
R.63 E., bears S.0°11'W., 10.54 chs. distant; an iron
post, 1 in. in dia., firmly set, and marked and witnessed
as described in the official record.

Cor. stands on steep SW. slope on top of a small rocky
spur sloping SW. about 4 chs. distant to end.