INDEPENDENT RESURVEY WEST BOUNDARY OF T.22 S.,R.64 E.

Chains	
	$\frac{1}{4}$ S12 | S7 1931
42.00	Top of ascent on E. slope; gradually descend.
52.45	Rocky draw, 35 ft. below top of ascent, drains E.; gradually ascend 35 ft. to
60.00	Low rocky ridge spur, bears NE. and S.60°W., 35 ft. above draw; gradually descend.
62.55	Head of draw, drains NW.; ascend rocky SW. slope 130 ft. to sec. cor.
80.00	On rocky SW. slope at base of gray ledges about 40 ft. high bearing N.20°W. and S.20°E.
	Set an iron post, 3 ft. long, 2 ins. in dia., 6 ins. in the ground on solid rock and supported by a large mound of stone for cor. of secs. 1,6,7, and 12, with brass cap marked
	T22S R63½E | R64E S1 | S6 S12 | S7 1931
	deposit a granite stone, 9x7x5 ins., marked with a cross (+) on one face at base of post.
	Land, rough and broken mountains draining NE.
	Soil, shallow rocky loam; 4th. rate.
	No timber.
	Undergrowth, creosote and chaparral.
	North, bet. secs. 1 and 6.
	Over broken mountainous land through creosote and chaparral undergrowth; ascend SW. slope over gray ledges.
3.10	Spur, 125 ft. above sec. cor., projects NW. from S.30°E.; descend steep and rocky NE. slope.
5.50	Ledge, 120 ft. high, bears S.30°E. and N.30°W. about 4 chs. distant to end.
11.75	Spur, 235 ft. below last spur, projects N.30°E.; descend along W. slope of spur.
23.70	Same spur, 70 ft. below last crossing, projects NW. about 4 chs. distant, thence N.; descend along E. slope.
30.30	Swale, 55 ft. below spur, drains E.; ascend rocky E. slope.